



Series	S-Series LFP	Warranty	See Warranty Terms
Volts	12	BCI	G31
Terminal Type	M8		
Included Hardware	M8 stainless bolts & washers		

### Charge

Charge Voltage Range	14.0 - 14.6V
Recommended End of Discharge Voltage	12.0 V
End of Discharge Protection Voltage	10.0 V
Recommended Charge Voltage	14.4 V

Recommended Charge Current		
-20~0°C (-4-50°F)	0.1C	14A
0~10°C (32-50°F)	0.2C	27A
10~35°C (50-95°F)	0.5C	68A
35~50°C (95-122°F)	0.2C	27A

### Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to  $\leq 0.05C$  (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	135 A
Max Continuous Discharge Current	135 A
Surge Current Limit	900 A (300ms)
Charge Temperature Range	-20°C~55°C (-4~131°F)
Discharge Temperature Range	-20°C~60°C (-4~140°F)
Storage Temperature Range	-5°~45°C (23~113°F)

### Capacity

Nominal Capacity	150 AH
Total Energy	1.92 kWh
Nominal Voltage	12.8 V

### Safety

- Cylindrical LiFePO4 cells (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

### Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Display & integrated controls
- Visual state-of-charge (SOC)
- External fuse access
- Internal heating for -20°C(-4°F)~0°C(32°F) charging
- Bluetooth Connectivity & dedicated App
- Maintenance-free operation

### Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Balance Protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

### 12V LFP Profile

### Specifications

	Weight	16.5 kg	35.3 lbs
	Length	33.1 cm	13.03"
	Width	17.1 cm	6.73"
	Height Inc. Term.	22.9 cm	9.02"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
Internal BMS Model	4S150ATX-V2
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	4 UNITS MAX
Parallel Connection	4 UNITS MAX
Connectivity	Up to 4S4P (48V configuration) or 1S6P

### Detailed Illustration

