



## Inverter Remote Control

Pure Sine Wave

Model  
S-R6-12

### Design Features

- Designed for use with 12V versions of SA, SK & ST Series of Pure Sine Wave Inverters with 12 VDC input
- Reverse override function
- 10 feet of connecting cable included
- Bar Meter Monitor for battery voltage and output power
- LED indicators for:
  - Over voltage protection
  - Under voltage protection
  - Over temperature protection
  - Over load protection
  - Power save mode
  - Inverter ON condition
  - Grid pass through condition (ST Series)

## 2 YEAR WARRANTY

<b>MODEL NO.</b>	<b>S-R6-12</b>		
<b>INPUT VOLTAGE</b>	12V Nominal Battery System Voltage		
<b>STANDBY CURRENT DRAW</b>	< 80 mA		
<b>OPERATING TEMPERATURE RANGE</b>	0°C to 40°C / 32°F to 104°F		
<b>STORAGE TEMPERATURE RANGE</b>	-30°C to 70°C / -22°F to 158°F		
<b>CONNECTING CABLE</b>	- 10 ft, 4 Conductors - 4P4C or 6P4C Modular Plugs - Straight Connection		
<b>DIMENSIONS, INCHES (W x D x H)</b>	5.1 x 1.02 x 4.7		
<b>DIMENSIONS, MM (W x D x H)</b>	130 x 26 x 120		
<b>WEIGHT (WITHOUT CABLE), g</b>	356		
<b>WEIGHT (WITHOUT CABLE), lbs</b>	0.8		
<b>FOR USE WITH SPECIFIC INVERTER MODELS (12V INPUT VERSIONS ONLY)</b>	SA-1000K	SK700	ST-1500
	SA-2000K	SK1000	
	SA-3000K	SK1500	
		SK2000	
		SK3000	

NOTE: Specifications are subject to change without notice

12003-S-R6-12-0413