

TOUGHFLEX™ WELDING CABLE



FEATURES

- Special stranding and packaging are available upon request
- Oil Resistant
- Resistant to Flame
- Customizable PermaPrint™ indent print that lasts a lifetime and inkjet print are available on all colors & sizes
- Halogen Free, all colors except green
- Cable meets the UL VW-1 flame test outlined in UL1581
- SAE J1127 Stranding

APPLICATIONS

- Secondary voltage resistance welding cable leads
- Temporary power uses
- National Electrical Code article 630 electric welders
- Power supply applications not exceeding 600 volts AC
- Copper meets SAE standards.

CONSTRUCTION

Highly flexible stranded No. 30 bare copper conductor insulated with a high grade RoHS compliant EPDM. A paper separator is utilized to enhance stripability. Maximum conductor operating temperature is 105°C in circuits not exceeding 600 Volts. Minimum temperature rating is -50°C. Class K stranding.

TOUGHFLEX™ WELDING CABLE



GAUGE	STRANDING	INSULATION THICKNESS		Nominal O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
8	7/24/.010	0.070	1.78	0.300	7.62	1000	87
6	7/37/.010	0.060	1.52	0.320	8.13	1000	113
4	7/52/.010	0.060	1.52	0.348	8.84	1000	147
2	12/52/.010	0.060	1.52	0.420	10.67	500	236
1	12/65/.010	0.080	2.03	0.503	12.78	500	313
1/0	19/52/.010	0.080	2.03	0.533	13.54	500	378
2/0	19/65/.010	0.080	2.03	0.586	14.88	500	463
3/0	19/81/.010	0.080	2.03	0.625	15.88	500	563
4/0	19/106/.010	0.080	2.03	0.720	18.29	500	734
250 MCM	19/133/.010	0.100	2.54	0.815	20.70	500	962

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS HEADQUARTERS
167 Greenfield Road
Lancaster, PA 17601

KALAS LOS ANGELES
28365 Constellation Road,
Unit B
Valencia, CA 91355

KALASWIRE.COM
P 717.336.5575
F 717.945.1002